

WIN-Slide 2

SLIDING SYSTEM for shutters weighing up to 80 kg



GUARANTEE
12 YEARS
SYSTEMS FOR
OUTDOOR USE



SLIDING



WIN-Slide 2 high-end sliding systems

■ COMPACT:

- reduced vertical space requirements across the range, with 3-c rectangular adjustment maintained. The brackets have a diagonal oblong holes for more stability

- new compact perimeter return pulley integrated into the end stop

■ TIME-SAVING: spacing between track fastening points increased by 50% (from 44 to 66 cm)

■ SAFETY: new end stop with 2 anchoring points in the track

■ INNOVATION: new camper ensuring panels open and close softly.



Installation
video



DESIGNER AND MANUFACTURER OF SLIDING SYSTEMS SINCE 1920

www.mantion.com

MANTION
SLIDING SYSTEMS



WIN-Slide 2 for panels up to 80 kg

HANGERS & ACCESSORIES

Reference	Description
11280XA2	1 hanger equipped with 4 rollers, pins mounted on ball bearings, A2 stainless steel M8 screws (59 mm). For panels operated manually, without synchronisation. Max. weight 80 kg/panel.
11280LXA2	Ditto, with M8 screws (93 mm) for synchronised and/or motorised panels.
0026XA2	A2 stainless steel plate to be screwed on edge. Panel thickness: 25 mm min.
0027XA2	A2 stainless steel bracket to be screwed on panel face (80 x 58 mm). Panel thickness: 28 to 36 mm.
11286XA2	Track stop with two anchoring points. Supplied with A2 stainless steel fasteners.



SOFTCLOSER

JUNE 2023	Softcloser for softly opening and/or closing doors. The softcloser automatically accompanies the panel to its open and/or closed position.
------------------	--

TRACKS & ACCESSORIES - single channel - 80 kg

11208/600*	Raw aluminium track, 39 x 36 mm cross section, L = 6 m.
11293	Adjustable, single, raw aluminium mounting bracket. Supplied with A2 stainless steel fasteners. Fastened every 660 mm at most.



PELMETS & END CAPS - single channel - 80 kg

For manually operated shutters

11263/600*	Raw aluminium pelmet, L = 6 m.
11266	Set of pelmet end caps 11263, including: 2 raw aluminium end caps, 2 pelmet fastening clasps, 8 A4 stainless steel fastening screws.

*other lengths on request



For synchronised and/or motorised shutters

11263L/600*	Raw aluminium pelmet, L = 6 m.
11266L	Set of pelmet end caps 11263L, for synchronised shutters, including: 2 raw aluminium end caps, 2 pelmet fastening clasps, 8 A4 stainless steel fastening screws.
11266M	Ditto for motorised shutters; contains an extra bracket for the end cap on the motor side.



Pelmet mounting

11269	Set of 5 anodised aluminium clasps for fastening pelmets onto brackets.
-------	---

TRACKS & ACCESSORIES - double channel or single shade screen

11208/600*	Raw aluminium track, 39 x 36 mm cross section, L = 6 m.
11293D	Adjustable, double, raw aluminium mounting bracket. Supplied with A2 stainless steel fasteners. Fastened every 660 mm at most.



PELMETS & END CAPS - double channel or single shade screen

For manual, synchronised and/or motorised shutters

11264L/600*	Raw aluminium pelmet, L = 6 m.
11267L	Set of pelmet end caps 11264L, for manual and/or synchronised shutters, including: 2 raw aluminium end caps, 2 pelmet fastening clasps, 8 A4 stainless steel fastening screws.
11267M	Ditto for motorised shutters; contains an extra bracket for the end cap on the motor side.

*other lengths on request



Pelmet mounting

11269	Set of 5 anodised aluminium clasps for fastening pelmets onto brackets.
-------	---

